

XMP-7300

4k Ultra Performance Media Player Technical Specification



Open Standards Supported

- HTML5, JavaScript, and CSS
- Android 4.4 API
- W3C SMIL for cross-platform management
- W3C Widgets for HTML delivery

Video formats supported

- H.264/AVC up to 2160p @24fps (3840x2160)
- MPEG-4 up to 1080p @60fps (1920x1080)
- MPEG-2 up to 1080p @24fps (1920x1080)
- MPEG-1 up to 1080p @60fps (1920x1080)
- VC-1 up to 1080p @30fps (1920x1080)
- H.265/HEVC: 4k @60fps (4096x2160) up to 100Mbps bit rate

Image format supported

- JPEG
- GIF
- PNG
- BMP

Audio format supported

- MPEG Audio (MP3)

Advanced Signage Features

- Remote commissioning
- AlwaysOn, AppLockto prevent unauthorized access
- StrongCache for continued playback even when network is not available

HTML5 Support

- Widgets for calendar, clock, news, weather, Twitter, and web page integration
- HTML5 technologies including CSS and Javascript
- WebKit-based browser engine, same as Google Chrome™ and Apple Safari® browsers

Digital Signage Features

- Multi-zone screen layout, transparent PNG overlay, and graphical scrolling ticker
- Auto-play starts playing scheduled contents automatically when power is re-established
- Automatic error recovery with built-in WDT
- Real-time clock with backup clock battery

Content Management

- SignApps Express Utility
- 3rd party solution (optional license)

Connectivity

- Wi-Fi: 802.11 b/g/n
- HDMI 2.0 (4096x2160 @60fps)
- Micro USB for ADB
- Gigabit Ethernet
- USB 2.0 x 2
- Bluetooth low energy beacon
- 3.5mm analog stereo audio out
- S/PDIF out
- Optional 3G/4G mobile module via USB

Local Storage

- 8 GB eMMC built-in
- Micro SD card slot (card replaces internal storage)

Mounting kit

- Built-in wall mount bracket

Supplied accessories

- HDMI cable
- External 2dB Wi-Fi antenna
- Velcro
- Power /Micro SD card brackets

Expansion Options

- 16GB/32GB micro SD/SDHC memory card

AC Adapter

- Input: 100-240V, 50-60 Hz, 0.5A Max.
- Output: 12V, 1.5A
- UL/FCC/CB/CCC/VCCI/PSE certified power supplies
- Interchangeable connector system includes US plugs (Option for EU, UK and AUS plugs)

Environmental

- Operating temperature: 0 to 50°C
- Humidity: 10 to 85% @ 45°C, non-condensing

Dimensions for Product and Package

- Size: 143.60 mm x 105.90 mm x 33.65 mm / 5.65" x 4.16" x 1.32" (143.60 mm x 128.13 mm x 33.65 mm / 5.65" x 5.04" x 1.32" with bracket)
- Weight: 478 g / 1.05 lbs.
- Outer Carton Size: 470mmx359mmx239mm/18.50"x14.13"x9.41"
- Units per Outer Carton: 10

Certifications

- CE/FCC/RoHS

Warranty

- 1-year limited parts & labor

Product Photos



Dynamic overlay

Twitter live feed



Calendar

Weather

Slideshow

SmartWidgets in HTML5
(Monitor not included)