



PoE Signboard with LED Bar Designed for Meeting Room

XDS-1078 10.1" Interactive All-in-one Signboard



Feature Highlight:

- 10-inch wide-view-angle touch display
- Compact design for easy table-top placement or wall-mount
- Professional memory management solution that prolongs memory lifespan
- Edge-mounted color LED light bars for conference room applications


Industry:



www.audiointegrate.nl

Technical Specification:

- HTML5/SMIL/Android 4.4
- 10.1" 1280 x 800 resolution
- Multi-touch screen
- 300-nits brightness
- Wide view angle
- Power over Ethernet
- Ethernet 10/100 Base-T
- 802.11 b/g/n WLAN



Signboard Comparison Chart



XDK-Series
Flexible Signboard Kit



Open Frame
Professional Open Frame



XDS-0548
5" Information
Signboard



XDS-1070
10.1" Commercial
Grade Signboard



XDS-1078
10.1" Interactive
All-in-one Signboard

Features					
One-wire installation via PoE	•	•			•
LED illumination door sign					•
Interactive touch screen			•		•
Easy wall mount				•	•
VESA MIS-D 75 mounting point		•		•	•
3G dongle module	Option	Option		Option	Option
NFC dongle module				Option	Option
Robust storage solution via eMMC	•	•	•	•	•
Fanless	•	•	•	•	•
Hardware watchdog timer	•	•	•	•	•
Smooth ticker	•	•	•	•	•
Management software					
Programming API	HTML5+SMIL+Android	HTML5+SMIL+Android	HTML5+SMIL+Android	HTML5+SMIL+Android	HTML5+SMIL+Android
3 rd party software	•	•	•	•	•
Media format					
Video format	H.264, MPEG 2/4 AVC	H.264, MPEG 2/4 AVC	H.264, MPEG 2/4 AVC	H.264, MPEG 2/4 AVC	H.264, MPEG 2/4 AVC
Max. video resolution	1920x1080, 30fps	1920x1080, 30fps	1920x1080, 30fps	1920x1080, 30fps	1920x1080, 30fps
Image format	JPEG, PNG	JPEG, PNG	JPEG, PNG	JPEG, PNG	JPEG, PNG
Max. image resolution	1920x1080	1920x1080	1920x1080	1920x1080	1920x1080
Audio format	MP3	MP3	MP3	MP3	MP3
Hardware specification					
Screen Size	10.1", 15.6", 18.5", 21", 23.6"	10.1", 15.6", 18.5", 21", 23.6"	5"	10.1"	10.1"
Max. screen resolution	Per panel selection	Per panel selection	800 x 400	1280 x 800	1280 x 800
Brightness (nits)	Per panel selection	Per panel selection	300	300	300
Viewing angles (H/V, CR>10)	Per panel selection	Per panel selection	140 x 120	160/160	160/160
Build-in speaker	N/A	N/A	1W x 1	2W x 2	2W x 2
Local storage	8GB	8GB	8GB	8GB	8GB
Wi-Fi/Bluetooth	802.11 b/g/n, BT4.0	802.11 b/g/n, BT4.0	802.11 b/g/n, BT4.0	802.11 b/g/n, BT4.0	802.11 b/g/n, BT4.0
I/O ports	HDMI out	HDMI out	Micro USB port	3.5mm stereo audio	HDMI out
	3.5mm stereo audio	3.5mm stereo audio	3.5mm stereo audio	USB ports	3.5mm stereo audio
	USB ports	USB ports	Micro SD card slot	ADB port	USB ports
	ADB port	ADB port	Reset button	Ethernet port	ADB port
	Ethernet port	Ethernet port		Micro SD card slot	Ethernet port
	MicroSD card slot	Micro SD card slot		Power jack	Micro SD card slot
	Power jack	Power jack		Reset button	Power jack
	Reset button	Reset button		Kensington lock	Reset button
					Kensington lock
Power adapter input	100V-240V	100V-240V	100V-240V	100V-240V	100V-240V
Power adapter output	Per panel selection	Per panel selection	5V2A	12V 1.5A	12V 1.5A
Operation temperature	0-40C	0-40C	0-40C	0-40C	0-40C
Humidity	5-85% @ 45 degree	5-85% @ 45 degree	5-85% @ 45 degree	5-85% @ 45 degree	5-85% @ 45 degree
	non-condensing	non-condensing	non-condensing	non-condensing	non-condensing
Certification	Per request	Per request	CE/FCC/RoHS	CE/FCC/RoHS	CE/FCC/RoHS
Warranty					
Parts & labor	1 year	1 year	1 year	1 year	1 year

This preliminary information is subject to change, please contact sales for information update.

PIO-102 GPIO Module

for XDS-1070/1078
Open Frame
XDK-Series

Plug-n-play


Ports

Dimension

Weight

Certification

Warranty



10 input ports
4 output ports
2.7" x 2.4" x 0.6" /
68 x 60 x 16 mm
150g / 0.7 lbs
RoHS
1 year



Bedrijvenweg 2
7161 AJ NEEDE
The Netherlands

T. +31 547 712 092
E. info@audiointegrate.nl
www.audiointegrate.nl