

<u>MODEL</u>	<u>No.Cores</u>	<u>Shielded (Y/N)</u>	<u>Min.CoreSize</u>	<u>Max Lenth</u>	<u>Con.Type</u>		
					<b>Mixer End (Cloud products only!)</b>	<b>Accessory or Mic End</b>	
LM1	9	Y	7/02 (i)	100m	9pin sub D	screw terminal	
RSL6	2	Y	7/02 (i)	100m	3 pin 5mm phoenix	screw terminal	
RL1 (products supporting remote source select)	1	Y	7/02 (i)	100m	3 pin 5mm phoenix	screw terminal	
RL1 (on products that do not (VCA-5)	2	Y	7/02 (i)	100m	3 pin 5mm phoenix	screw terminal	
ME1	CAT5 STP	Y	CAT5 STP	100m	RJ-45 (iv)	RJ-45 (iv)	
LE1	CAT5 STP	Y	CAT5 STP	100m	RJ-45 (iv)	RJ-45 (iv)	
BE1	CAT5 STP	Y	CAT5 STP	100m	RJ-45 (iv)	RJ-45 (iv)	
CDR1	CAT5 STP	N	CAT5 STP	100m	RJ-45	RJ-45	
	+ optional 2 core power cable to external PSU	N	16/02 (ii)	100m	Varies	2.1mm power coax	
CDR1F	CAT5 STP	N	CAT5 STP	100m	RJ-45	RJ-45	
	+ optional 2 core power cable to external PSU	N	16/02 (ii)	100m	Varies	plug in phoenix screw terminal	
<b><u>Paging Mics</u></b>							
<b>Using Analogue Interface</b>							
PM1	2 (+2 optional access pair)	Y	Standard mic cable.	100m	Varies	screw terminal	
PM-4	5 core +1 if powered from mixer	Y	7/02 (i)	100m	plug in phoenix screw terminal	screw terminal	
	+ 2 core mic cable	Y	Standard mic cable.	100m	Varies	screw terminal	
	+ optional 2 core power cable to external PSU	N	16/02 (ii)	100m	Varies	2.1mm power coax or screw terminal	
PM-8	9 core +1 if powered from mixer	Y	7/02 (i)	100m	plug in phoenix screw terminal	screw terminal	
	+ 2 core mic cable	Y	Standard mic cable.	100m	Varies	screw terminal	
	+ optional 2 core power cable to external PSU	N	16/02 (ii)	100m	Varies	2.1mm power coax or screw terminal	
PM-12	12 core +1 if powered from mixer	Y	7/02 (i)	100m	plug in phoenix screw terminal	screw terminal	
	+ 2 core mic cable	Y	Standard mic cable.	100m	Varies	screw terminal	
	+ optional 2 core power cable to external PSU	N	16/02 (ii)	100m	Varies	2.1mm power coax or screw terminal	
PM-16	17 core +1 if powered from mixer	Y	7/02 (i)	100m	plug in phoenix screw terminal	screw terminal	
	+ 2 core mic cable	Y	Standard mic cable.	100m	Varies	screw terminal	
	+ optional 2 core power cable to external PSU	N	16/02 (ii)	100m	Varies	2.1mm power coax or screw terminal	
<b>Using Digital Interface (between mics or to DCM-1)</b>							
PM-4	CAT5 STP	N	CAT5 STP	100m	RJ-45	RJ-45	
	+ optional 2 core power cable to external PSU	N	16/02 (ii)	100m	Varies	2.1mm power coax or screw terminal	
PM-8	CAT5 STP	N	CAT5 STP	100m	RJ-45	RJ-45	
	+ optional 2 core power cable to external PSU	N	16/02 (ii)	100m	Varies	2.1mm power coax or screw terminal	
PM-12	CAT5 STP	N	CAT5 STP	100m	RJ-45	RJ-45	
	+ optional 2 core power cable to external PSU	N	16/02 (ii)	100m	Varies	2.1mm power coax or screw terminal	
PM-16	CAT5 STP	N	CAT5 STP	100m	RJ-45	RJ-45	
	+ optional 2 core power cable to external PSU	N	16/02 (ii)	100m	Varies	2.1mm power coax or screw terminal	

SPECS:

- (i) 7/02 = 7 strands of 0.2mm dia, which is approx 0.22mm<sup>2</sup> or AWG32
- (ii) 16/02 = 16 strands of 0.2mm dia, which is approx 0.5mm<sup>2</sup> or AWG24
- (iii) CAT5 UTP = Unshielded Twisted pair
- (iv) CAT5 STP = Shielded Twisted Pair