

TECHNICAL SPECIFICATIONS



A 200

A professional power amplifiers are designed in order to meet the increasing demand of low power amplifiers for installation market.

These stereo power amplifiers have complete protection functions and superior performance. **A200** 2 channel power amplifiers: 200W rated power per channel at 4Ω . Screw terminal speaker connectors and balanced Phoenix input connectors. Ultra slim body, fan cooling system.

	A 200
Output power	Rated $200 \text{ W} + 200 \text{ W} (4 \Omega), 130 \text{ W} + 130 \text{ W} (8 \Omega)$
Power supply	AC 115 V/230 V 50/ 60Hz ±10 %, with selection
Outputs (each channel;)	Screw terminal block
Inputs (each channel;)	Phoenix connector (balanced) 10 k Ω , 0,775 V
Frequency response	25 Hz - 25 kHz
THD	< 0,03 %
Signal / noise ratio	> 100 dB
Damping factor (1kHz and below)	$>$ 400 at 8 Ω
Controls	Front: AC switch, channel 1 & 2 gain knobs
Indicators	Power ON; Signal (1 per channel); Clip (1 per channel); Protect
Dimensions	482 mm x 45 mm x 320 mm
Weight	9 kg
Mounting	19″ rack
Colour	Black (RAL 9017)

CE ROHS AMC Baltic

Neries krantinė 14A, LT-48397 Kaunas, Lithuania Phone +370 37 308585, 308584 Fax +370 37 308583 E-mail info@amcpro.lt Web www.amcpro.lt