

TECHNICAL SPECIFICATIONS



COM

COM – weatherproof column loudspeakers for voice and background music reproduction.

COM320 is a two way column loudspeaker with built-in 2x3" woofer and 1,5" tweeter. **COM340** has a built-in 4x3" woofer and 1,5" tweeter. Wide frequency range, 100V transformer with power taps, aluminum body, IP66, for indoor and outdoor use. Typical applications: warehouses, factory buildings, workshops, transport terminals and car parking lots.

	COM 320	COM 340
Rated power	20 W	40 W
Transformer power taps	20 W - 10 W	40 W - 20 W
Sensitivity	89 dB (1 W/1 m)	90 dB (1 W/1 m)
Maximum SPL	102 dB (Pmax/1 m)	106 dB (Pmax/1 m)
Frequency response	135 Hz – 20 kHz	135 Hz – 20 kHz
Protection	IP 66	IP 66
Dimensions	370 mm × 110 mm x 97 mm	550 mm × 110 mm x 97 mm
Driver dimensions	2 x 3" (76,2 mm) woofer, 1,5" (38,1 mm) tweeter	4 x 3" (76,2 mm) woofer, 1,5" (38,1 mm) tweeter
Weight	2,6 kg	3,6 kg
Material	Aluminum	Aluminum
Colour	White (RAL 9016)	White (RAL 9016)