

TECHNICAL SPECIFICATIONS



COM HP

COM HP – High Performance weatherproof column loudspeaker for background music and speech reproduction.

Two way system with build-in 0,8" tweeter. IP66 rating. Wide frequency responds and high sensitivity. Special mounting bracket designed for precise angle alignment during the mounting.

Typical application: railway stations, subways, churches, factory buildings, warehouses, parking lots and outdoor markets. Fully appropriate for indoor and outdoor installations.



Above: included mounting hardware

unit: mm

	COM 20 HP	COM 30 HP
Rated power	20 W	30 W
Transformer power taps	20 W - 10 W - 5 W - 2,5 W	30 W - 15 W - 7,5 W - 3,75 W
Sensitivity	92 dB (1 W/1 m)	93 dB (1 W/1 m)
Maximum SPL	105 dB (Pmax/1 m)	108 dB (Pmax/1 m)
Frequency response	120 Hz – 20 kHz	110 Hz – 20 kHz
Dispersion at 1000 Hz	180° (H), 45° (V)	180° (H), 40° (V)
Protection	IP 66	IP 66
Dimensions	585 mm × 125 mm x 110 mm	775 mm × 125 mm x 110 mm
Driver dimensions	4 x 3,5" (88 mm) woofer, 0,8" (20 mm) tweeter	6 x 3,5" (88 mm) woofer, ,0,8" (20 mm) tweeter
Weight	5 kg	7 kg
Material	Aluminum	Aluminum
Colour	White (RAL 9016)	White (RAL 9016)