

# PC 5T / PC 8T Plastic ceiling loudspeakers

## TECHNICAL SPECIFICATIONS




### PC 5T / PC8T

**PC T - ABS plastic ceiling loudspeakers with built-in 100V transformer with power taps.**


Excellent full range sound, used where a combination of high quality background music and public address are required. These loudspeakers are designed to be quickly and simply installed into false ceilings. Wide sound dispersion and innovative neutral design makes these loudspeakers useful in a variety of applications, restaurants, bars, cafes, shops, offices, moles and large public spaces for background music and speech announcements.

	PC 5T	PC 8T
Rated power	10 W	20 W
Transformer power taps	10 W - 5 W - 2,5 W - 1,25 W	20 W - 10 W - 5 W - 2,5 W
Sensitivity	88 dB (1 W/1 m)	88 dB (1 W/1 m)
Maximum SPL	98 dB (Pmax/1 m) at 15694 Hz	101 dB (Pmax/1 m) at 15249 Hz
Frequency response	90 Hz – 20 kHz	80 Hz – 20 kHz
Dispersion at 1000 Hz	120° conical	120° conical
Driver dimensions	5" (130 mm) woofer, 0,5" (13 mm) tweeter, coaxial	8" (200 mm) woofer, 0,5" (13 mm) tweeter, coaxial
Dimensions	ø 190 mm × 70 mm	ø 245 mm × 95 mm
Weight	1,1 kg	2,1 kg
Material	Plastic	Plastic
Colour	White (RAL 9016)	White (RAL 9016)

**PC 5T**



**PC 8T**



unit: mm