SL 30 Spherical loudspeaker



TECHNICAL SPECIFICATIONS



SL 30


SL 30 - Plastic spherical loudspeaker with 6.5" (165 mm) woofer and 1" (24 mm) tweeter.

Coaxial speaker, 100 V transformer and 8 Ω power tap, power selector. Wide frequency range, conical sound dispersion. Wire rope in the cable – for safety. Two colour choice. **SL 30** spherical loudspeaker is great for covering large areas from high ceiling and is ideal for both speech and background music.

| | SL 30 |
|------------------------|---|
| Rated power | 30 W (8 Ω) |
| Transformer power taps | 30 W - 15 W - 7,5 W - 3,75 W |
| Sensitivity | 89 dB (1W/1 m) |
| Maximum SPL | 108 dB (Pmax/1 m) at 2511 Hz |
| Frequency response | 100 Hz – 20 kHz |
| Dispersion at 1000 Hz | 160° conical |
| Driver dimensions | 6,5" (165 mm) woofer × 1" (24 mm) tweeter |
| Dimensions | ø 275 mm x 2000 mm |
| Weight | 3 kg |
| Material | ABS plastic housing, grill - metal |
| Colour | White (RAL 9016), Black (RAL 9017) |

unit: mm

SL 30







Neries krantinė 14A, LT-48397 Kaunas, Lithuania **Phone** +370 37 308585, 308584 **Fax** +370 37 308583 **E-mail** info@amcpro.eu **Web** www.amcpro.eu