

TECHNICAL SPECIFICATIONS



Talk

TALK gooseneck microphones with condenser or dynamic capsule. It can be used with TALK ST stands for fixed installation as desktop microphone.

Talk C – condenser gooseneck microphone with a built-in phantom power adapter and low cut filter. High sensitivity, wide frequency response and elegant construction. Professional XLR connector is integrated into the metal body. Supplied with windscreen.

Talk D – dynamic gooseneck microphone with robust body and steel grill capsule basket. Designed for paging purposes. Professional XLR connector is integrated into the metal body. Supplied with windscreen.

Talk ST microphone stands for XLR gooseneck microphones with on/of switch.

	Talk C	Talk D	Talk ST
Element	Permanently polarized condenser	Dynamic	
impedance	250 Ω	500 Ω	
Sensitivity	46 dB	76 dB	
Frequency	50 Hz–18 kHz	150 Hz–12 kHz	
Connector	3-pin male XLR	3-pin male XLR	<i>Microphone input:</i> 3-pin female XLR <i>Cable:</i> 3-pin male XLR
Characteristics			Plug-in metal desk stand with on/off switch for microphones with XLRM connectors
Dimensions	485 mm (length)	425 mm (length)	45 mm × 110 mm × 140 mm
Weight	115 g	176 g	856 g
Material			Die-cast metal, rubber feet
Colour	Black	Black	Black



Talk ST desk stand with on/off switch



Talk ST cable connector



Talk C close-up



Talk D close-up